

96 x 96 panel mount multifunction WEIGHT indicator

- This controller allows to control various industrial weighing processes like Filling, Integration, Bulk-Weighing, Over/Under, Weight Tare, etc.
- It is available in two versions: standard and with DSP.
- This weighing indicator with DSP has advanced digital filters (IIR and FIR) that allow to obtain weight data readings even faster and with higher precision.

FEATURES:

- ✓ Accuracy class: III - 6000d concerning EN45501 / OIML R76 (T.C: 100312001).
- ✓ Accuracy classes for automatic weighing: 0.2, 0.5, 1 and 2, according to OIML R107 (EC: 151700002).
- ✓ Accuracy classes for automatic weighing: X(0.2), X(0.5), X(1) and X(2), according to OIML R061 (EC: 151700002).
- ✓ Accuracy classes XI, XII, XIII, XIII, Y(a), Y(b) according to OIML R51 (EC: 151700002).
- ✓ Certified indicator firmware according to guide WELMEC 7.2 (Certificate num. 151700003).
- ✓ Load Cell Input with a 24 bits A/D Sigma-Delta converter.
- ✓ 2 Displays of 7 Segments: 1 of 6 Digits, and 1 of 8 Digits and 14 Led Indicators.
- ✓ 2 Opto-isolated Serial Ports: RS232C and RS422 or RS485.
- ✓ 20 Keys Keyboard to use and program the controller.
- ✓ 4 PNP or NPN Opto-isolated Inputs.
- ✓ 4 Relay outputs
- ✓ Power Supply: 115 Vac / 220 Vac.
- ✓ Dimensions: 96x96x139mm.



OPTIONS:

- ✓ 2nd RS232 serial port.
- ✓ Ethernet 10/100M Base T communication port.
- ✓ WIFI communication port.
- ✓ USB 2.0 communication port.
- ✓ Opto-isolated Encoder Input.
- ✓ Time and date.
- ✓ 24 Vdc Power supply.
- ✓ PS2 / PC Keyboard Input.
- ✓ Opto-isolated analogical Output: 0-20mA, 4-20mA, 0-5Vdc, 0-10Vdc.











ADDITIONAL FEATURES and OPTIONS (DSP):


- ✓ Load Cell Input with a *high speed* 24 bits A/D Sigma-Delta converter.
- ✓ Option: 2nd RS485 serial port.
- ✓ Option: internal USB 2.0 communication port.



Multifunction weight indicator DW-BG

OPERATING MODES:

Reference	Description	
	FillerAdd	Additive filling, bagging: 1 product up to 3 rates, unload and alarms.
	FillerAddAdv	Additive filling, bagging: 1 product up to 2 rates, unload, alarms and 10 selectable programs.
	FillerMan	Manual filling, bagging: indicator for Defect – Ok – Excess weight.
	FillerSub	Dispensing filler (lost-in-weight): 1 product up to 3 rates, reload and alarms.
	FillerAso	Associative filling: 1 product up to 3 rates, unload and alarms.
	Bulk	Bulk weighing: up to 2 rates, unload, alarms, ticket.
	Check	Check-weighing: In motion weighing, checks the weighing of a product.
	Quality	Quality control: Batches verification for prepacked product, based on OIML R87 (prepacked products quantity).
	Limits	Limits, alarms, totalizing, integration: up to 4 weighing set point, configurable inputs, variables printing, peaks memories.
	Integra	Beld weighing: Allows to totalize, fix setpoints, flow rate by hour, etc.



DW-BG Rear view